

DYNAMIC

**LIGHT
DUTY**



**18
MONTH
WARRANTY**



Electrical specification

Voltage:	12V
Capacity C ²⁰ :	70 Ah
Cold cranking current:	680 CCA [SAE]
Reserve Capacity:	116 min

Mechanical specification

Dimensional group:	L3
ETN reference:	657D
Dimensions ^A in mm (LxWxH):	278x175x190
Cell Layout:	1
Terminal Type:	A

Container

Case	Material	Polypropylene
	Bottom hold-down	B13
	Colour	Black

Lid	Material	Polypropylene
	Cover design	SMF
	Colour	Black

Vent caps	Material	Polypropylene
	Type	SMF
	Colour	Black

Handles	Material	Polypropylene
	Position	Top - on lid
	Colour	Black


Battery classification

Water consumption	Charge retention	Vibration resistance	Endurance Level
W3	C2	V1	E1


Weight^B

Battery weight in kg:	11.40
Acid weight in kg:	5.80
Total battery weight in kg:	17.20

Layout



Hold-down



Separator

Type	PE
------	----

- ^{A.} Height taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.
^{B.} Weight may vary ±5%.

Date of update: 11.03.2024